

16DWV-880

DWV Series for Diesel Generator application

POWER RATING

Engine Speed	Type of Operation	Engine Gross Power	
		kW	PS
1500 rpm	Prime Power	705	959
	Standby Power	780	1061
1800 rpm	Prime Power	790	1074
	Standby Power	875	1190

- The engine performance is as per ISO 3046. Type of operation is based on ISO 8528.
- Prime power is available for an unlimited number of hours per year in a variable load application.
- The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

Engine Specifications

○ Engine Type	V-type, 4 strokes, water-cooled, Turbocharged air-to-air intercooled
○ Combustion type	Direct injection
○ Cylinder Type	Wet liner
○ No. of Cylinders	16
○ Bore x stroke	128 x 142 mm
○ Displacement	29.24 liter
○ Compression ratio	14.6 : 1
○ Firing order	1-15-6-12-8-5-16-7- -11-4-9-2-14-10-3-13
○ Injection timing	16 °BTDC
○ Dry weight	Approx. 2100 kg
○ Dimension(LxWxH)	1950 x 1389 x 1288 mm
○ Rotation	Anti-clockwise (Face to the flywheel)
○ Fly wheel housing	SAE NO. 0
○ Fly wheel	SAE NO. 18
○ Ring Gear Tooth	160 EA

Fuel Consumption Data

Speed Rating	(Liter/ Hour)			
	1500 rpm		1800 rpm	
	Prime	Standby	Prime	Standby
100% Load	705 kW	780 kW	790 kW	875 kW
75% Load	126.1	139.6	144.2	159.7
50% Load	92.5	102.3	105.7	117.1
25% Load	58.9	65.1	67.3	74.5

Fuel System

○ Injection pump	Direct Injection type
○ Governor	Electronic type
○ Feed pump	Mechanical Type
○ Injection nozzle	Multi-hole type
○ Injection pressure	27 MPa (270 kg/cm ²)
○ Fuel filter	Full Flow, Cartridge Type
○ Used fuel	Diesel fuel oil

Mechanism

○ Type	Overhead valve
○ Number of valve	Intake 1, exhaust 1 per Cylinder
○ Valve lashes at cold	Intake. 0.3 mm Exhaust 0.4 mm

Lubrication System

○ Lub. Oil Grade	AFI - CF-4 oil
○ Lub. Oil Pan Capacity	Min 60, Max 78 liter
○ Max. allowable Oil Temp	120 degree C.
○ Oil pressure	Min. 300 kPa (3.0 kg/cm ²) Max. 650 kPa (6.5 kg/cm ²)
○ Oil Consumption Rate	≤ 1.2 g/kWh

Cooling System

- Cooling method Fresh water forced type
- Water Pump Centrifugal, belt driven
- Water capacity 26 liter (engine only)
- Max. Water Temp 99 degree C.
- Thermostat Open 71°C / Full 83°C
- Water Pump flow 650 liter/min
- Cooling Fan Blade 8, Dia 1450 mm

Intake & Exhaust System

- Max air restriction Clean 2 kPa / Dirty 5 kPa
- Exhaust back pressure Max 6 kPa

Electric System

- Charging generator 28 V × 45 A (1260 W)
- Voltage regulator Build-in type
- Starting motor 24 V × 11 kW
- Battery Voltage 24 V
- Battery Capacity 200 Ah

Engineering Data

		1500 rpm		1800 rpm	
○ Media Flow		Prime	S/B	Prime	S/B
Combustion Air	m3/min	55.8	61.6	63.8	70.6
Exhaust Gas	m3/min	145.0	160.3	165.7	183.6
Cooling Fan	m3/min				
○ Heat Rejection		1500 rpm		1800 rpm	
to Exhaust	kW	564	623	633	701
to Coolant	kW	212	234	237	263
to Intercooler	kW	162	179	182	201
to radiation	kW	63	69	70	79

Conversion Table

in. = mm × 0.0394	lb/ft = N.m × 0.737
PS = kW × 1.3596	U.S. gal = lit. × 0.264
psi = kg/cm ² × 14.2233	kW = 0.2388 kcal/sec
in ³ = lit. × 61.02	lb/PS.h = g/kW.h × 0.00162
HP= PS × 0.98635	Cfm = m3/min × 35.336
lb = kg × 2.20462	

Engine Layout & Dimension

